

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 September 2005 (22.09.2005)

PCT

(10) International Publication Number
WO 2005/088013 A1

(51) International Patent Classification⁷:

E01B 29/24

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/IT2004/000125

(22) International Filing Date: 16 March 2004 (16.03.2004)

(25) Filing Language: Italian

(26) Publication Language: English

(71) Applicant (for all designated States except US): CEM-BRE S.P.A. [IT/IT]; Via Serenissima, 9, I-25135 Brescia (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BAREZZANI, Gualtiero [IT/IT]; Via Zanardelli, 130, I-25062 Concesio (IT). BRAGA, Cesare [IT/IT]; Via Maria Malibran, 7, I-25131 Brescia (IT).

(74) Agents: SINISCALCO, Fabio et al.; Jacobacci & Partners S.p.A., Via Senato, 8, I-20121 Milano (IT).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BE, BY, CR, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A DEVICE FOR THE APPLICATION AND/OR REMOVAL OF RAIL CLIPS



WO 2005/088013 A1

(57) Abstract: A device (1) for the application and/or for the removal of elements for the connection of a rail to a railway track sleeper, comprising at least one lever (2, 3) mounted on a frame (4) in a rotatable manner around an axis of rotation (5, 6), and equipped with at least one pressure organ (7, 8) adapted to engaging the connecting element, and at least one cylinder-piston group (9) adapted to driving the lever (2, 3) in order to assemble or disassemble the connecting element. The cylinder-piston group (9) comprises a cylinder body (10) and a sliding piston (11) housed within the cylinder body (10) and moveable with respect to the cylinder body (10) under the action of pressurised fluid. At least one first (12, 14) and second (13, 15) stop surfaces interact in such a manner as to form a stop device (16, 17) for stopping the lever (2, 3) in a defined position with respect to the frame (4), wherein the stop surfaces are formed, the one (12, 14) on the piston (11) and the other (13, 15) on the cylinder body (10) of said cylinder-piston group (9).